

www.ETRVEHICLES.com







December 31, 2024

Mr. Donnie Finkelstein, Fleet Manager Charlotte County Fire and EMS 26581 Airport Road Punta Gorda, Fl 33982

We are pleased to provide you with the following pricing, shop order, and chassis specifications for the purchase of two (2) new 2026 Freightliner M2 std. 2 door cabs with Custom AEV Type I Ambulance module. Pricing is based on purchasing these units from the Florida Sheriffs Contract Bid No. FSA23-VEF17.0: Fire & Recuse Vehicles, Boats & Equipment, Item #611 Freightliner M2 Diesel AEV modular box 172" x 95" 68".

## PRICING:

- Included in the above price: Your present graphics/chevron layout with window perf, Ferno monitor bracket LP15, ETR trash can/holder, FLIR K2 camera, retractable lanyard, truck battery charger, desk top charger, 1 extra battery, Stryker Power Pro 2 High Conf., Stair Chair 6252, and Activtek Induct 500 Active Pure Technology.
- The above price is based on availability of 2026 chassis or February 28, 2025
- Terms: Payment in full is due upon delivery of each unit. Upon payment, ETR, L.L.C. shall furnish the County a "Statement of Origin" or the necessary validated documents required for title application.

## **OPTIONAL PRICING:**

- Stryker Power Pro 2 High Configuration \$34,967.00 each
- Stryker Stair Chair model 6252 \$5,367.00 each

Sincerely,

Jerry Michaluk President/CE)

Corporate Office 700 S. French Ave. Sanford, FL 32771 T: 407-339-6737 Toll Free: 884-612-8148



Georgia Office Juliette, GA. 31046 Toll Free: 844-612-8148

DESCRIPTION	QTY	\$
Florida Sheriff Contract Bid NO FSA23-VEF17.0 Item #611	1	\$ 278,244
2025 Freightliner M2 106MD, 2-dr Reg Cab - Dealer Supplied	1	
M2 Reg Cab POWER TRAIN / FUNCTIONAL ITEMS - 6.7L 2022	1	\$ -
Batteries: (2) Group 31, Min 2190 CCA - 6.7L	1	\$ -
Terminals, Battery: 3/8" LUG, Copper Alloy - (2) Batt	1	\$ -
Exhaust System	1	\$ -
Exhaust Termination: Passenger Side, Vertical. Muffler-term behind Cab	1	\$ -
Fuel Tank: Driver Side Under Cab	1	\$ -
Urea Tank: 6 US Gallon, Single Under Cab Driver's Side	1	\$ -
GVWR: 20,000 pounds	1	\$ -
Rear Suspension: 12,000# Air-liner w/PING tanks, Kneeling 6.7L	1	\$ -
Rear Axle: Meritor RS-15-120 Single Speed - 15,000# 6.7L	1	\$ -
Rear Axle Ratio: 4.56:1	1	\$ -
DUMP ACTIVATION: Trailing rear access door.	1	\$ -
DUMP ENABLE SWITCH: Located in center CAB console	1	\$ -
DUMP ACTIVATION OTHER: Deactivate with O2 Door Open	1	\$ 75
Kneeling Rear Air Suspension Control Freightliner M2	1	\$ -
DEF Urea Surcharge, Emission Compliance Fill up	1	\$ 75
M2 Reg Cab EXTERIOR ITEMS - 6.7L	1	s -
Air Horns: Dual 24.5" Hadley Stutter tone, (1) ea side hood	1	\$ -
Tires, Front: Random Make 245/70R 19.5 16 Ply (Road tread)	1	\$ -
Tires, Rear: Random Make 245/70R 19.5 16 Ply (Road tread)	1	\$ -
Wheels: 19.5 x 6.75 Polished Forged Aluminum	1	\$ - \$ -
Centers & Lug Nut Covers for Front & Rear OEM Alum Wheels Rear 8.25 Hub 10 lug	2	\$ -
M2 Reg Cab INTERIOR ITEMS - 6.7L	1	\$ -
	1	\$ -
CAB Air Conditioning: OEM w/ Heat, defrost	1	\$ -
Cab Interior Color: Opal Gray	1	<u> </u>
Cab Door Locks: Power	1	\$ -
OEM Freightliner key fobs NOT included		\$ -
Tire Pressure Monitoring System: None	1	\$ -
Fuel Surcharge, M2-4500, Any-WB Chassis, Med Duty	1	\$ 142
BODY Generation 10	1	\$ -
Body Build Information	1	\$ -
ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4"	1	\$ -
Body, Mod: Med Duty, 172" x 96" x 72" Interior HR - 6" Body Drop M2	1	\$ 2,887
Headroom: 74/72" Finished Interior - Ducted A/C	1	\$ -
Compartment and Entry door Full length Stainless Steel Hinges std	1	\$ -
Perko Air Vent: Exterior, Used for Body Venting	1	\$ 124
Compartment Construction: STANDARD, Unless Specified Otherwise	1	\$ -
Compt Floors: Sweep-out, even with bottom door jamb	1	\$ -
Compartment floor thickness .125" standard	1	\$ -
Compartment Ventilation - Flap style #VT-2495-A01, STD	1	\$ -
Talk through, Cab to Mod Window (T1) Medium Duty With Sliding Window		\$ -
Cab Roof Support: 3/16" x 3" Steel Plate, Per Engineering Drawing	1	\$ -
Body Drop: 6" Both Sides, Ahead of Rear Wheels	1	\$ 373
Curb side Entry Door (CSE): 84.812 High x 31 Wide -Medium duty	1	\$ -
Step Well, CURBSIDE Entry Door, 2-Step Diamond Plate	1	\$ 217
ILOS Lt, Step Well: 3" Kin#4302S LED stainless steel surface mount housing	1	\$ 51
Light, Step Well #2 : NONE	1	\$ -
Compt Door Check:SPRING type DOOR-CHECK1211 (12 Lb) Other compt ILOS EA	9	\$ 1,177
Door Swing Angle: Set to 90-100 degrees	9	\$ -
Side Entry Door Check: SPRING DOOR-CHECK3012 (30# Spg) ILOS	1	\$ 177
Door Swing Angle: Set to 90-100 degrees	1	\$ -
M-1 Compt (LF): 72 HR, 77" H x 16" W x 21" D	1	\$ -
Compartment Construction: STANDARD Diamond Plate	1	\$ -
Compartment Door Panel: Diamond Plate	1	\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
Compt Floor: Sweep-out, even with bottom door jamb.	1	\$ -
Compartment floor thickness .125" standard	1	\$ -
Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch	1	\$ -
Compartment boor. Silvott book, Forward hinged 2 point taten		
	1	\$ -
(1) Door Hold Opens: Grabber Style, each door 4 1/2" tall	1 2	\$ - \$ 491
(1) Door Hold Opens: Grabber Style, each door 4 1/2" tall   M1 Dividers, (2) Vertical, Full compartment height, alum, Fixed	2	\$ 491
(1) Door Hold Opens: Grabber Style, each door 4 1/2" tall   M1 Dividers, (2) Vertical, Full compartment height, alum, Fixed   Strap: 2" Webb Seatbelt buckle chrome footman loops	2	\$ 491 \$ -
(1) Door Hold Opens: Grabber Style, each door 4 1/2" tall   M1 Dividers, (2) Vertical, Full compartment height, alum, Fixed	2	\$ 491

Compartment Construction: STANDARD Diamond Plate	1	\$ -
Compartment Door Panel: Diamond Plate	1	\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
Compartment floor thickness .125" standard	1	\$ -
Compt Floor: Sweep-out, even with bottom door jamb.	1	\$ -
- Compartment floor thickness .125" standard	1	s -
Doors, Compartment, DOUBLE DOORS (std)	1	\$ -
	1	1
Compt Door Check: Spring Check	+	l'
Door Swing Angle: Set to 90 degrees	1	\$ -
M-2 Shelf, Adjustable, Ext: .125 Alum, 1.5" Upward lip	1	\$ -
Shelf Bracket: 90 Deg with Slotted Holes	1	\$ -
Light, Compartment: Maxxima LED 18" , EA, ILOS	1	\$ 56
Light, Compartment: Maxxima LED 18" , EA, IATS	2	\$ 322
Condenser, 12V:VALEO/ACC #25067, Dual Fan, Low Profile roof mount ILOS-MD/ HWP	1	\$ 1,540
Roof top limb guard for Condenser Painted to match roof	1	\$ 472
· · · · ·	1	+ ·
Roof Condenser Height Impact up to 7.5"		\$ -
Standard Conduit: 1-1/2"", with pull wire	1	\$ -
CONDUIT ORIGINATION POINT: M-2 compartment	1	\$ -
CONDUIT TERMINATION POINT: Behind A/A Board (Panel)	1	\$ -
- M-2.5 Compt (LWW): 16.5" H x 41.75" W x 21" D	1	\$ 2,664
Compartment Construction: STANDARD Diamond Plate	1	\$ -
	1	ċ
Compartment Door Panel: Diamond Plate		\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
Compt Floor: Sweep-out, even with bottom door jamb.	1	\$ -
Compartment floor thickness .125" standard	1	\$ -
Compartment Doors: DOUBLE DOORS, ILOS single	1	\$ 482
Compt Door Check: Spring Check	1	\$ -
Door Swing Angle: Set to 90-degrees	1	\$ -
Light, Compartment: Maxxima LED 18" , EA, ILOS	1	\$ 56
		ļ'
M-3 Compt (LR): 71" H x 41.75" W x 21" D	1	\$ 1,267
Compartment Construction: STANDARD Diamond Plate	1	\$ -
Compartment Door Panel: Diamond Plate	1	\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
Compt Floor: Sweep-out, even with bottom door jamb.	1	\$ -
Compartment floor thickness .125" standard	1	s -
Compartment Doors: DOUBLE DOORS, ILOS single	1	\$ 482
	-	3 402
Compt Door Check: Spring Check	1	\$ -
Door Swing Angle: Set to 90 degrees	1	\$ -
Shelf, Adjustable, Ext: .125 Aluminum, 2" Upward Lips	1	\$ 268
Shelf Bracket: 90 Deg with Slotted Holes	1	\$ -
Light, Compartment: Maxxima LED 18" , EA, ILOS	1	\$ 56
Light, Compartment: Maxxima LED 18" , EA, IATS	2	\$ 322
M-4 Rear Curbside Bench Compt: 16" H x 14.1" W x I/O Access	1	\$ 2,464
		1 1
Compt Floor Sill: Stainless Steel From O2 Rack to Door	1	\$ -
Compartment Door: SINGLE DOOR, 1-point Latch	1	\$ -
Light, Compartment: Maxxima LED 18" , EA, ILOS	1	\$ 56
- M-5 Compt (RR): 18.75" H x 43" W x 21.0"D	1	\$ -
Compartment Construction: STANDARD Diamond Plate	1	\$ -
Compartment Door Panel: Diamond Plate	1	\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
· · ·	+	<u> </u>
Compt Floor: Sweep-out, even with bottom door jamb.	1	\$ -
Compartment floor thickness .125" standard	1	\$ -
Compartment Doors: DOUBLE DOORS, ILOS single	1	\$ 482
Compt Door Check: Spring Check	1	\$ -
Door Swing Angle: Set to 90-degrees	1	\$ -
Light, Compartment: Maxxima LED 18" , EA, ILOS	1	\$ 56
M-7 Compt (RF): 56.25" H x 29.5" W x 33" Above Floor & 23" D (Below FL)		+.
ivi-/ Compt(nf). 30.23 ΠΧΖΆ.3 W Χ 33 ADOVE FIOUI & Z3 D (BEIOW FL)	1	\$ -
	-	
Compartment Construction: STANDARD Diamond Plate	1	\$ -
	1	\$ -
Compartment Construction: STANDARD Diamond Plate	+	,
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard	1	\$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.	1 1 1	\$ - \$ - \$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.   Compartment floor thickness .125" standard	1 1 1	\$ - \$ - \$ - \$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.   Compartment floor thickness .125" standard   Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch	1 1 1 1	\$ - \$ - \$ - \$ - \$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.   Compartment floor thickness .125" standard   Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch   Compt Door Check: Spring Check	1 1 1 1 1 1	\$ - \$ - \$ - \$ - \$ - \$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.   Compartment floor thickness .125" standard   Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch   Compartment Door Check: Spring Check   Door Swing Angle: Set to 90 degrees	1 1 1 1 1 1 1	\$ - \$ - \$ - \$ - \$ - \$ - \$ -
Compartment Construction: STANDARD Diamond Plate   Compartment Door Panel: Diamond Plate   Compartment Finish: Diamond Plate Standard   Compt Floor: Sweep-out, even with bottom door jamb.   Compartment floor thickness .125" standard   Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch   Compt Door Check: Spring Check	1 1 1 1 1 1	\$ - \$ - \$ - \$ - \$ - \$ -

I		14	
Light, Compartment: Maxxima LED 36" , EA, ILOS	1	\$ 137	
M-8 Drawer (RF): Batt, 13.5" H x 29.5" W x 21" D	1	\$ 2,220	
Compartment Construction: STANDARD Diamond Plate	1	\$	-
Compartment Door Panel: Smooth Aluminum	1	\$	
Compartment Finish: Diamond Plate Standard	1	\$	-
Drawer Front: 2-point latch	1	\$	-
Rear Access Doors: 46 3/4" Wide x 60 5/8" High	1	\$	-
BODY PROTECTION AND TRIM PACKAGE: M2	1	\$	-
Wire/Hose Cover : Diamond Plate, Between Cab & Module	1	\$	-
Pass-Thru cab mounted wind deflector - Aluminum Diamond Plate	1	\$	-
Right Side Under cab Cover: Diamond Plate, Pass Side W/ 2 steps M2/KW Charlotte	1	\$	-
Left Side Driver's Fuel Tank/Def tank Cover W/ 2 steps Reg Cab M2 ILOS Charlotte	1	\$	-
UREA Cover: Diamond Plate	1	\$	-
Bumper, Rear:Medium Duty Hd Framed w/DP pontoon covers	1	\$	-
Step, Center:2" x 7" Bar Grate, flip-up, recessed T1 ILOS	1	\$ 532	
Flip-step Bumper : Rubber Skirt Rail on Kick Plate	1	\$ 228	
Dock Bumpers: Rubber 2 1/4" H x 16" W x 2" Thick	1	\$ 226	
Wheel Size: 19.5" (Must match what is on chassis)	1	\$	
Fenders, Rear: Rubber Extruded, Black	1	\$	
Skirt Rails: Extruded Rubber	1	\$ 264	
'		\$ 204	
Corner Caps: 24.0" High, Alum Diamond Plate	1	\$	
Front Stone Guards: 24.0" High, Alum Diamond Plate	1	\$	-
Rear Kick Plate: Polished Aluminum Diamond Plate	1	\$	-
Rear Recovery Eyes: (2) Cast Iron 1 3/16" center eye Paint Black	1	\$ 566	
Eye Access Holes: (2) 5 inch Dia , Align w/ eyes	1	\$	-
Recessed Tag Area: Polished Aluminum Diamond Plate	1	\$	-
Location: Centered in the kick plate	1	\$	-
Tag Light: Kinequip LED #132703C	1	\$	-
(2) Rear Door Hold Opens: Grabber Style, 1 on each door	1	\$	-
Mud Flaps Front: NONE	1	\$	-
Mud Flaps Rear: Modular, Rubber, Medium Duty units AEV LOGO	1	Ś	-
Front Turn, Whelen M6 Series w/arrow, LED, Pair, IATS	1	\$ 590	
Location: Front of Module, Below Light Bar	1	\$	
M6 Series Flange, Chrome Plated, Std: Each	2	ė	_
		Ś	
CORNER CAP LED ICC/WARNING LIGHTS	1	<u> </u>	
Front Corner Cap LED ICC/Warning Lights: Warnings RED/WHITE	1	\$	-
Front Center ICC Lts: (3) AMBER Kinequip LED No 112401A,	1	\$	-
Front ICC Lt Guards: NONE	1	\$	-
Rear Corner Cap LED ICC/Warning Lights: Warnings RED/AMBER	1	\$	-
Rear Center ICC Lts: (3) RED Kinequip LED No 112401R	1	\$	-
Rear ICC Lt Guards: NONE	1	\$	-
ICC Warning Lights Switched: Primary Only	1	\$	-
LED Patient on Board, Exterior, NONE	1	\$	-
LED Lights, Door Panel Warning, Interior	1	\$	-
Amber LED POB Light, Each	5	\$ 419	
Red/White LED Light, Each, NONE	1	Ś	-
White LED Light, Each, NONE	1	Ś	-
Red LED Light, Each, NONE	1	\$	_
Blue LED Light, Each, NONE	1	Ġ	_
Lights Switched with Entry Door Switch	1	\$	_
Underbody Ground Lights : NONE		\$	
, ,	1	\$	-
Tail Lights, Whelen LED Combinations , ILOS, Non FORD chassis	1	\$	-
Side Marker Lights: (2) RED Peterson #V423KR, In Bumper Pontoons (Med Duty ONLY)	1	\$ 808	
Additional Tail Lights: Whelen M6 Installed at Rear Window Level	1	\$	-
Whelen M6 Series, Tail Lights	1	\$	-
Stop/Tail, Whelen M6 Series, LED, Pair RED LED/ RED LENS	1	\$ 210	
Turn, Whelen M6 Series, LED, Pair Amber LED, Amber LENS	1	\$ 199	
M6 Series Flange, Chrome Plated, Std: Two Pair	1	\$	-
Whelen M6 Series, Tail Lights	1	\$	-
Stop/Tail, Whelen M6 Series, LED, Pair RED LED/ RED LENS	1	\$ 210	
Turn, Whelen M6 Series, LED, Pair Amber LENS	1	\$ 199	
Back up, Whelen M6 Series, LED, Pair	1	\$ 346	
M6 Series Flange, Chrome Plated, Std: Three Pair	1	\$	-
Third (3rd) Brake Light: Kinequip KFL-3BLO1 LED		\$	
			-
	1	<u> </u>	
Light is to steady burn, no flash  SCENE/FLOOD LIGHTS (LED-M9 Series)	1 1	\$	-

			1.	
F	langes: Above M9 Scene lights, Incorporated into lights	1	\$	-
L	eft Flood Activate: Left Flood Switch	1	\$	-
Righ	nt Scene Lights: (2) LED-M9ZC, Chrome flange Whelen	1	\$ 1,251	
J F	langes: Above M9 Scene lights, Incorporated into lights	1	\$	-
F	ight Flood Activate: Right Flood Switch and open CSE Door	1	\$	-
	r Load Lights: Built into Rear Light Bar	1	Ś	-
	ctivate: Rear Flood Switch, Reverse and Lead RA Door	1	\$	
		1	\$ 181	
	Activation: Rearward Left and Right scene lights. come on w/ Reverse		\$ 191	
	ent Ventilation System:Static Intake, 4 inch Power Exhaust STD	1	\$	-
Secondar	y Heat/AC: Danhard 125VAC System, 50-3001Cool ONLY	1	\$ 9,023	
Digi	tal RTH 221B Thermostat, battery powered	1	\$ 253	
Dan	hard Compressor/ Condensor Mounted Underbody Forward of Axle	1	\$	-
Dan	hard Front Grille Cover- Std Size Aluminum with Black Coating	1	\$	-
I Dan	hard Additional Underbody Drain Pan - Charlotte County	1	\$ 252	
	) SYS:VALEO/ACC HotWeathPkg, Ducted Ceiling - Vertical, Type 9, M2, KW	1	\$	_
		1	\$	-
	COMPRESSOR: Secondary OEM engine compressor		<u> </u>	
	rmostatic Switch Pre-set with 24 inch temp probe OFF 34F on 38F	1	\$ 150	
AC	Evaporator: VALEO/ACC (AC/Heat unit) w/ dual fans - STD	1	\$	-
C	condensation Drain Pan: Internal ABS	1	\$	-
H	leater Hoses: EPDM - Nomex Rubber (per Ford QVM)	1	\$	-
	C Hoses: Burgaflex Dual Clip, Hose and fitting system	1	Ś	-
	ide Plenum Grille, Return Air: Customer/Dealer Supplied	1	¢	-
		1	4	
	C Register Panels: (Std)		\$	-
L	oucted AC Delivery: insulated & foil wrapped, 10 registers	1	\$	1-1
Hell	a Relay Connector: Installed	1	\$	1-1
AC :	secondary compressor manifold VALEO/ACC M-2& others	1	\$	-
The	rmostat, Rear A/C, Digital, VMUX Includes Front Also	1	\$	-
Espar Hea	ter System: None	1	\$	-
	ANELS : ACM Gloss White - Medium Duty	1	\$	
		1	\$ 911	
	ne Lts, LED: Whelen ,(4) Streetside, (4) Curbside #80C0EHCR			
Tim	er: Electronic, 15 Min with momentary switch	1	\$ 191	
T	imer to Power: Street side DOMES, High intensity	1	\$	-
(2) :	Speakers: Stereo, patient compartment, in center pad	1	\$ 129	
IV	look No 1: CPI A2012 (Surface Mount), ILOS	1	\$ 132	
	LOCATION: Over Knee/Waist area, Between Dome Light #3 & 4 primary patient on COT	1	Ś	-
I IV F	look No 2: CPI A2012 (Surface Mount), ILOS	1	\$ 132	
	·	1	÷ 132	
<del> </del>	LOCATION: Over Knee/Waist area, Between Dome Lt. #3 & 4 secondary patient on S/B		\$	
	essed C/S Grab Rail, ceiling: 1.25 Dia 3 pt, 72in, Yellow Antimicrobial	1	Ş	-
Insu	ılation: Circumferential PKG, Single Layer Reflective w/ Air cell core	1	\$	-
Blue	e Block foam ENTRY DOOR Insulated: 2" Thick IATS	1	\$ 418	
Insu	llation Sound Deadening: Generation 10 Floor	1	\$	-
I Blue	e Block foam WALLS/CEILING Insulated PKG: 1" Thick, IATS Reflective	1	\$ 1,685	
	owell Insulation: None	1	\$	
			\$ 6,070	
	t Bar: Whelen4500 88" LED, Custom Charlotte Co			
	ight Bar LOCATION: Box FRONT / Surface mount	1	\$	-
RR I	ight Bar: Whelen 88"LED Custom ETR Charlotte County	1	\$ 6,724	
L	ight Bar LOCATION: Box REAR / Surface mount	1	\$	-
F	lear lightbar flash pattern please define	1	\$	-
	ear Load Lights: Switched REAR FLOOD	1	\$	-
	LED WARNING LT SYSTEM - M2 LTD	1	\$	_
			·	
	her: None, All M Series LED's Are Programmable	1	\$	-
	lash Pattern: None, Internal Light Head Flasher	1	\$	-
V	Varning Light SWITCH: center console, Primary / Secondary	1	\$	-
(2)	Grille Lights: Whelen M7 Series, LED	1	\$	-
(	irill or Int. M7 Chrome Flange Each	2	\$	-
	Fille or Int M7 Red LED, Clear Lens-Prog. Each	2	\$ 485	
	Intersection Lights: Whelen M7 Series, LED	1	Ś	_
			\$	
	irill or Int. M7 Chrome Flange Each	2	<u> </u>	-
	Frille or Int M7 Red LED, Clear Lens-Prog. Each	2	\$ 485	
DEL	ETE (1) Center Front Warning Light	1	\$	-
DEL	ETE (2) Front Warning Lights	1	\$	-
	Upper Side Body Lights: Whelen M9 Series, LED	1	\$	-
	//9 Series Flange, Chrome Plated, Std: Two Pair	1	\$	-
		4		
	ight: Whelen M9, LED, RED LED/CLEAR Lens, Programmable ILOS		\$ 3,233	
	Rear Intersection Lights: Whelen M6 Series, LED	1	\$ 131	
I I N	1/16 Series Flange, Chrome Plated, Std: Each	2	\$	-
1		1	\$	

		T.
Light: Whelen M6, LED, RED LED/CLEAR Lens, Flash, ILOS	2	\$ 616
DELETE (2) Rear Warning Light	1	\$ -
(2) Additional Rear Body Lights: Whelen M6 Series, LED	1	\$ 131
M6 Series Flange, Chrome Plated, Std: Each	2	\$ -
LED M6 Red - Pair	1	\$ -
Light: Whelen M6, LED, RED LED/CLEAR Lens, Flash, ILOS	2	\$ 616
DELETE (1) Rear Center Warning Light	1	\$ -
Additional Warning Lts : (2) Whelen M2 Lights	1	\$ 644
Flanges:(2) Chrome, M2 Lights	1	\$ -
Light:s Whelen M2, LED, RED LED/CLEAR Lens PAIR -flash IATS	1	\$ 700
Location: On REAR Body Outboard of Rear Doors	1	\$ -
LED Program Switch: NONE	1	\$ -
Customer Supplied Part(s) : Yes See account	1	\$ 957
Retractile Power Cord, 659 (CORD-659) : Installed	9	\$ 2,280
Custom design wood console included in Order	1	\$ -
Install "Do Not Step" Labels Under Hood On Passenger and Driver Side	1	\$ 93
Headlight Flasher Special switching	1	\$ 96
Hand Held Spot Light: Eagle Eye, Rubber Housing	1	\$ 319
	1	\$ -
Hard Wire Light Under Dash on Passenger Side		\$ -
Batteries: 2 - Battery System - Medium duty std.	1	\$ -
Battery Make: (2) OEM per chassis type.	1	\$ -
Batt Loc: (T9) All Batteries M-8	1	\$ -
Battery Switch: OEM Paddle Switch	1	\$ -
Batteries Wired: Parallel for higher amperage	1	\$ -
Dash Light: NONE	1	\$ -
Cabinet Interior Lights: None	1	\$ -
POWER Door Locks: Module Doors - Freightliner M2 Mod	1	\$ -
Door Locks, Tied into OEM System Freightliner M2	1	\$ 132
DrLkSw: SPDT Momentary, (1) On A/A Board	1	\$ 93
Magnadyne Keyless entry Fob: Unlocks Chassis and Mod Doors	1	\$ -
Door Lock Switches : Integrated in Interior Entry door Handles	1	\$ -
ONLY the following doors shall have power door locks:	1	\$ -
Electric Door Lock: M1A Compt: (NONE)	1	\$ -
Electric Door Lock: (M-1) Left Front Compartment	1	\$ 206
	1	\$ 206
Electric Door Lock: (M-2) Left Middle Compartment		<del>l'</del>
Electric Door Lock: (M-2.5) Left Wheel Well Compt.	1	\$ 206
Electric Door Lock: (M-3) Left Rear Compartment	1	\$ 206
Electric Door Lock: (M-4) Rear O2 Compartment	1	\$ 206
Electric Door Lock: Rear Access Doors	1	\$ 206
Electric Door Lock: (M-5) Right Rear Compartment	1	\$ 206
Electric Door Lock: Curbside Access Door	1	\$ 206
Electric Door Lock: (M-7) Right Front Compt	1	\$ 206
Remote Keypad #1 (Vertical): Installed	1	\$ 512
Location: On Chassis on "A" Piller (See Drawing)	1	\$ -
Remote Keypad #2: Horizontal Installed	1	\$ 512
Location: Curbside Rear Above M4 Compartment	1	\$ -
Door Unlock Switch, Momentary, Exterior, hidden	1	\$ 185
Location: Under M1 Compartment in Sealed Box	1	\$ -
Back-up Alarm: OEM	1	\$ -
Cut Off Switch: Thru VMUX System	1	\$ -
Exception to 3.14.6 Cancel switch for back up alarm - EXCEPTION to CAAS	1	\$ -
Circuit Board, 12V: Multiplex Weldon V-Mux, Freightliner	1	\$ 4,828
Voltage Monitor, Weldon V-MUX, w/ Warning Light	1	\$ -
Circuit Protection, 12V: FET - Auto-reset	1	\$ -
Cab Console Panel: Weldon V-MUX Vista IV #1	1	\$ -
Back Up Camera: Installed Ext over Rr Doors - ASA Adjustable White	1	\$ 553
Camera Color: White	1	\$ -
VMUX Vista panel mounted attached in Freightliner M2 upper overhead pocket	1	\$ 244
Patient Area Panel: Weldon V-MUX Vista IV #2	1	\$ -
Patient Area Weldon VMUC Vista IV Switch Panel:	1	\$ -
Switch Panel Located: Streetside A/A	1	\$ -
Patient area switch panel mounted :flat to action wall std	1	\$ -
2nd Patient Area Switch Panel: NONE	1	\$ -
		12
		Ś -
3rd Patient Area Switch Panel: NONE	1	Y

Cab Console : FL-M2	1	\$ -
Volt and Amp meters: Digital, VMUX Systems	1	\$ -
Engraved LOGO: None	1	\$ -
Add-on Console: Custom Storage Area	1	\$ 362
Customer Radio: Space for CustomerSuppliedRadio Heads	1	\$ -
Glove Storage: None	1	\$ -
Add On Console Finish: Gray Mica ILOS	1	\$ 163
Ground Straps, Module to Frame: (Qty 4) Braided	1	\$ -
		<u> </u>
Inverter: Vanner LIFESINE 1100 Pure Sine Wave, w 55watt 3 stage charger	1	\$ 2,079
Portable Equip Charging Circuits: Included in Inverter	1	\$ -
PREWIRE LOCATION: (1)Cab Console, (1) Behind A/A	1	\$ -
Portable Equip Pwr Source: Ignition and/or Shoreline	1	\$ -
Battery Charger/Conditioner: 55A - Built into Inverter	1	\$ -
Built-in Battery Charger: Enable - Wire to Batteries	1	\$ -
Inverter Location: M-2 (LFM) Compartment	1	\$ -
On Ceiling ILOS	1	\$ -
		<u> </u>
Lexan Cover: Over Breaker Box Only	1	\$ 81
Low Voltage Buzzer: Installed, Multiplex units	1	\$ -
Radio Power No 1: 40A, Pos and Neg, 8 awg Wires With Buss Bar	1	\$ -
Radio Power Source: Battery Switch Hot	1	\$ -
(2) Buss Bars 150 Amp,Dual Bus Plus 20 Stud 5 Gang 1/4"	2	\$ 284
LOCATION: Inside Cab Center Console	1	\$ -
Radio Power No 2: 40A, Pos and Neg, 8 awg Wires With Buss Bar	1	\$ -
	1	\$ -
Radio Power Source: Battery (Constant) Hot	-	+
(1) Buss Bar 150 Amp, Dual Bus Plus 20 Stud 5 Gang 1/4"	1	\$ 142
LOCATION: Inside Cab Center Console	1	\$ -
Radio Power No 3: 40A, Pos and Neg, 8 awg Wires With Buss Bar	1	\$ 94
Radio Power Source: Battery Switch Hot	1	\$ -
(2) Buss Bars 150 Amp,Dual Bus Plus 20 Stud 5 Gang 1/4"	2	\$ 284
LOCATION: Behind Action Area Board	1	\$ -
Radio Power No 4: 40A, Pos and Neg, 8 awg Wires With Buss Bar	1	\$ 94
Radio Power Source: Battery (Constant) Hot	1	\$ -
(1) Buss Bar 150 Amp,Dual Bus Plus 20 Stud 5 Gang 1/4"	1	\$ 142
LOCATION: Behind Action Area Board	1	\$ -
Coaxial Cable, No 1: Type RG-58U, No connectors	1	\$ -
ORIGINATION POINT: Above Left Front Dome Light	1	\$ -
Port Plate: None - Access thru left front dome light	1	\$ -
TERMINATION POINT: Center Console w/ 48" Tail	1	\$ -
		+'
Coaxial Cable, No 2: Type RG-58U, No connectors	1	\$ 53
ORIGINATION POINT: Above Right Front Dome Light	1	\$ -
Port Plate: None - Access thru right front dome light	1	\$ -
TERMINATION POINT: Behind Action Area Box w/ 48" Tail.	1	\$ -
Coaxial Cable, No 3: Type RG-58U, No connectors	1	\$ 53
ORIGINATION POINT: Above Second Dome Light on Left	1	\$ -
Port Plate: None - Access thru second dome light on left	1	\$ -
TERMINATION POINT: Center Console w/ 48" Tail	1	\$ -
		+'
Coaxial Cable, No 4: Type RG-58U, No connectors	1	\$ 53
ORIGINATION POINT: Above Third Dome Light on Left	1	\$ -
Port Plate: None - Access thru third dome light on left	1	\$ -
TERMINATION POINT: Behind Action Area Box w/ 48" Tail.	1	\$ -
Coaxial Cable, No 5: Type RG-58U, No connectors	1	\$ 53
ORIGINATION POINT: Above Third Dome Light on Right	1	\$ -
Port Plate: None - Access thru third dome light on right	1	\$ -
		7
TERMINATION POINT: Behind Action Area Box w/ 48" Tail.	1	\$ -
Coaxial Cable, No 6: Type RG-58U, No connectors	1	\$ 53
ORIGINATION POINT: Above Rear Dome on Curbside	1	\$ -
Port Plate: None - Access thru rear C/S dome light	1	\$ -
TERMINATION POINT: Center Console w/ 48" Tail	1	\$ -
Radio Brackets: Customer Supplied prior to production, Installed	1	\$ 62
	1	\$ 121
Ethernet Cable: Customer Supplied prior to production, Installed		<u> </u>
Portable Charger Bracket: Customer Supplied Supplied Pior to production	1	\$ 93
Patient Area Radio : None	1	\$ -
Intercom, Newmar, w/ Black Handset, Cab to patient area	1	\$ 1,053
125V SHORE LINE AND OUTLETS	1	\$ -
Shore Line Inlet: 20A Super Auto Eject, ILOS	1	\$ 662
Shore time mice. 20A Super Auto Eject, 1605		
Inlet location: Aft of Left Front compartment	1	Ś -

			lo 450
	Indicator Light, Shore line: Weather proof, power by SL, Green	1	\$ 150
$\longrightarrow$	Auto Eject Mounting Plate, Metal Painted	1	\$ 193
	Painted Part- Painted Special color to match Body	1	\$ 128
	Cover, Yellow, Shore Line Inlet : 20A Super Auto Eject, STD	1	\$ -
	Inpower Timer: VCM-05-01SF, Installed	1	\$ 129
	<del>-</del>	1	\$ -
	Shore Line Inlet No.2: 20A Super Auto Eject, IATS	1	\$ 702
	Inlet location: Aft of Left Front compartment	1	\$ -
-	Removable Shoreline Installed with twist lock 20 Amp plugs for service EACH	1	\$ 177
-+	Indicator Light, Shore line: Weather proof, power by SL, Green	1	\$ 150
+	Cover, Blue, Shore Line Inlet : 20 A Super Auto Eject, ILOS	1	\$ 59
+	**125 Volt OUTLETS**		<u> </u>
		1	\$ -
$\longrightarrow$	125 VAC Outlet, No 1: 15A, Hospital Grade, IVORY	1	\$ -
	LOCATION: Bottom of O1 Cabinet Facing Attendant Seat (See Drawing)	1	\$ -
	Outlet mounting ORIENTATION: Vertical	1	\$ -
	125 VAC Outlet, No 2: 15A, Hospital Grade, IVORY	1	\$ -
	LOCATION: RF ALS, (See Drawing)	1	\$ -
-	Outlet mounting ORIENTATION: Vertical	1	\$ -
-	125 VAC Outlet, No 3: 15A, Hospital Grade, IVORY	1	\$ 172
+	LOCATION: Cab Console on 3/4" Wall in Box Out on Passenger Side	1	\$ -
$\longrightarrow$	•		
	Outlet mounting ORIENTATION: Vertical	1	\$ -
$\longrightarrow$	**INTERIOR 12 Volt OUTLETS**	1	\$ -
	12 Volt outlets	1	\$ -
	12V Outlet, No 1: Power Point Single - Wire thru Med Isolator	1	\$ -
	LOCATION: Action Area, standard location	1	\$ -
	Outlet mounting ORIENTATION: Vertical	1	\$ -
	Power Source: Medical Isolator , Battery (CONSTANT) Hot	1	\$ -
	12 V Outlets, Double Receptacle (SOCK-04C), IATS	1	\$ 107
-+	Power Source: Medical Isolator , Battery (CONSTANT) Hot	1	¢
$\longrightarrow$			÷
	LOCATION: RF ALS, Top Corner of Wall #2 Near Wall #1 Next to 125 Outlet	1	\$ -
$\longrightarrow$	12V Outlet, DUAL USB Fast 4.8A,. 2.4 A per slot Round IATS EACH	1	\$ 156
	LOCATION: RF ALS, Top Corner of Wall #2 Near Wall #1 Next to 125 Outlet	1	\$ -
S	Siren: Federal PA-300-012MSC, ILOS, M-2	1	\$ 415
	Siren Spkr: CPI, Bumper Recessed, SA5403, M2 ILOS	1	\$ 59
	Siren / Horn Switch:	1	\$ -
	Air Horn System: OEM Supplied and Installed	1	\$ -
	Horn Discharge ENABLE: Both Cab Doors Closed	1	s -
	·	1	\$ 1,016
I`	Mica Colors: Gloss Gray D355-01 over Stainless Steel		
$\longrightarrow$	Mica Stripe (Belt): Gloss Charcoal/Slate D91-01	1	\$ 901
	Stainless Steel - FACE of Squad Bench	1	Ş -
	Stainless Steel - Lower Face of Wall Cabinet - Included	1	\$ -
P	Polycarbonate Type/Color: Lexan - Gray Secure Latch	1	\$ -
	Window Handles: Full Length Extruded	1	\$ -
	Att Seat: EVS,Comfort 1780 Dove Gray, Vacuum Form, Per4Max Black belt	1	\$ -
-	BASE: Swivel base for EVS Seat Option 8 position ILOS	1	\$ 289
<del></del>	AC CABINET: Evaporator, Custom Behind Att Seat Facing Rear of Truck W/1" Lip	1	\$ 145
		1	\$ 1,002
-+	CURBSIDE UPPER: Over S/B, Mods Wood cabinet, White Interior IATS		1
$\longrightarrow$	Cabinet K1 & K2: (2) Openings with flush center divider	1	\$ 161
	Door: Single Flip Up 3/8" Lexan	2	\$ -
	Hinges: Reel Torque	2	\$ -
	Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated	2	\$ 112
(	Glove Storage Cabinet, Over Entry Doors: None	1	\$ -
<del>-  </del>	CURBSIDE REAR: Rear of S/B, Mods, 3 glove	1	\$ 1,062
IC		1	ś -
<del> </del>	Cabinet M : (1) Opening	т т	
	Cabinet M : (1) Opening   Doors: Cabinet Secure Latch Sliding Window   Additional   -40 lbs		\$ 399
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs	1	\$ 399
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type	1	\$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate	1 1 1	\$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet	1 1 1 1	\$ - \$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense	1 1 1	\$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet	1 1 1 1	\$ - \$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense	1 1 1 1	\$ - \$ - \$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated	1 1 1 1 1	\$ - \$ - \$ - \$ 56
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated  F Cabinet, Behind Att Seat: Cabinet "H"/(Elec Cab) Facing Rear of Truck   Plastic Vent: (2) Total, 1 column x 8 row, Vent 01	1 1 1 1 1 1	\$ - \$ - \$ 56 \$ - \$ -
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated  F Cabinet, Behind Att Seat: Cabinet "H"/(Elec Cab) Facing Rear of Truck   Plastic Vent: (2) Total, 1 column x 8 row, Vent 01   Door, Single Solid Flush Fitted Electrical Area	1 1 1 1 1 1 1 1	\$ - \$ - \$ 56 \$ - \$ 5
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated  F Cabinet, Behind Att Seat: Cabinet "H"/(Elec Cab) Facing Rear of Truck   Plastic Vent: (2) Total, 1 column x 8 row, Vent 01   Door, Single Solid Flush Fitted Electrical Area   TRIM: U-shaped Door, J-trim opening	1 1 1 1 1 1 1 1 1	\$ - \$ - \$ - \$ 56 \$ - \$ - \$ 56
	Doors; Cabinet Secure Latch Sliding Window Additional -40 lbs   Shelf Track: Small alum Unistrut type   (1) Shelf: Shelf: Adjustable, Mica over substrate   Cabinet L: 3-Glove dispenser cabinet   Door: Overlay , 3/8" Lexan W/Reel Torque Hinges ILOS - 3-glove dispense   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated  F Cabinet, Behind Att Seat: Cabinet "H"/(Elec Cab) Facing Rear of Truck   Plastic Vent: (2) Total, 1 column x 8 row, Vent 01   Door, Single Solid Flush Fitted Electrical Area	1 1 1 1 1 1 1 1	\$ - \$ - \$ 56 \$ - \$ 5

Check the specified Walk through Door type (Station 5)	1	\$	-
Cabinet I-1: Custom	1	\$	-
Door: Single Flip Up 3/8" Lexan With Reel Torque Hinges	1	\$	-
Hinges: Reel Torque	1	\$	-
   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated	1	\$ 56	
Cabinet I-2: Custom From Floor to I-1 Cabinet	1	¢	_
· ·		¢ 204	
Door, Single Solid, Flush Fitted: W/ Lexan Insert	1	\$ 384	
   TRIM: U-shaped Door, J-trim opening,	1	\$	-
Hinge Orientation: RIGHT	1	\$	-
12" Secure latch installed on left side of door	1	\$	-
Stowage rating label Secure Latch 12" Single Handle on Door 40 pounds applied	1	\$	-
Hinge, ALS DOOR: Butt Style Hinges	1	Ś	-
Outside Access: Thru M-7 (RF) Compartment door.	1	Ġ	_
Interior: Diamond Plate	1	\$	
'		\$ 6	
   Cabinet I-3: DELETE, Combine with I2 Cabinet	1	\$	-
Right Rear Cabinet: NONE	1	\$	-
SQUAD BENCH: Medium Duty	1	\$	-
   Bio-waste/Sharps No 1: Custom With Old Style Sliding Lexan Window	1	\$	-
Doors, Sliding Lexan, Mitered AL Assy: Standard Non-compliant to J3058 ILOS	1	\$ 118	
   Full Length Extruded additional handle to facing door of all slider window	1	\$ 18	
	1	¢ 10	
Non-Compliant to 3.11.3 J3058, cabinets Not Tested, to SAE J3058 No Rating		2	
LOCATION: At head of Squad Bench	1	\$	-
SHARPS & TRASH CONTAINER: Kendall # 8970 (2) Gallon ILOS	2	\$	-
Storage Under Lid - Configure to Custom Bench With O2 Storage	1	\$	-
Squad Bench Lids: Split - 2-section	1	\$	-
Hinge, Squad Bench Lid(s): Piano Syle Hinges ILOS	1	\$	-
Lid Checks: Gas shock, Dual Action	2	\$	-
· ·	2	4	
   Latch, Squad Bench Lid: Slam Action Paddle, W keeper		\$	-
   Stowage rating label - Squad bench interior, entire area 80 lbs	2	\$	-
Edge Trim, Lids: Band w/ Laminate and J-Trim Protection	1	\$	-
O2 Viewing Window	1	\$	-
Restraint Net, Black, 7 point detachable, at head of S/B, Mod	1	\$	-
 Miscellaneous Squad Bench Options: Select from list	1	Ś	-
TOP CABINETS, - Med Std	1	Ś	_
		Ś	
   Cabinet A: Custom Above M3 Compartment	1	7	-
Doors; Cabinet A Secure Latch Restocking Sliding Window Top hinged -30 lb	1	\$ 399	
Cabinet Interior Lights: None	1	\$	-
Cabinet B1: Top Middle	1	\$	-
Shelf Track: Small alum Unistrut type	1	\$	-
(1) Shelf: Adjustable with Alum Trim	1	Ś	-
Doors; Cabinet B1 Secure Latch Restocking Sliding Window Top hinged	1	\$ 399	
	1	\$	
Cabinet Interior Lights: None		-	
- Cabinet B2: Top Forward	1	\$	-
Shelf Track: Small alum Unistrut type	1	\$	-
(1) Shelf: Adjustable with Alum Trim	1	\$	-
Doors; Cabinet B2 Secure Latch Restocking Sliding Window Top hinged	1	\$ 399	
Cabinet Interior Lights: None	1	Ś	-
 WALL CABINET: No CPR Seat and No Telemetry Area	1	\$	_
		<u> </u>	-
· · · · · · · · · · · · · · · · · · ·	1		
Action Area: Extended	1	\$	
Action Area: Extended   1/2" Solid Surface A/A Tray	1	\$ 1,601	
Action Area: Extended		+	-
Action Area: Extended   1/2" Solid Surface A/A Tray	1	+	-
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML	1	+	
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE	1 1 1	\$ 1,601 \$ \$	-
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom	1 1 1 1	\$ 1,601 \$ \$ \$ \$	-
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type	1 1 1 1 1	\$ 1,601 \$ \$	
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim	1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$	-
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound	1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$	
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim	1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$	
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound	1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$	
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE	1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat	1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS	1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated	1 1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated   Side Seat: NONE (DELETE)	1 1 1 1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated	1 1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated   Side Seat: NONE (DELETE)	1 1 1 1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	- - - - - - - - - -
Action Area: Extended   1/2" Solid Surface A/A Tray   Gibraltar (Solid Surface) Material COLOR: Northern Melange 9195ML   Action Area Board: Mica Covered (Color Keyed)   Cabinet C: DELETE   Cabinet D: Custom   Shelf Track: Small alum Unistrut type   (1) Shelf: Adjustable with Alum Trim   Doors; Cabinet D Secure Latch Sliding Window -40 pound   Cabinet E: DELETE   Cabinet F: DELETE   Cabinet O1: Custom W/ CD Player, 125 Outlet and Danhard Thermostat   Door: Single Overlay Lexan Hinged Right With Piano Hinge ILOS   Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated   Side Seat: NONE (DELETE)   Telemetry Area: NONE (DELETE)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	\$ 1,601 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	

		1.	
   S/B: (3) Sec patient restraints - 5" Sleeves By Hinge	1	\$	-
Mod Single Color VAC Form Tombstone Backrest with Separate Headrest std each	1	\$	-
Single Color Backrest and Headblock Dove Each	1	\$	-
Exhaust at Right Front I-1 Cabinet to be Static Air (No Fan Installed)	1	\$	-
Sub Floor, 3/4" Plywood, Standard	1	\$	-
 Flooring: Lonplate II - #424 TX (Textured) Gun Powder	1	\$ 679	
   Flooring Main Edge: 3" Recessed (1/2" deep) roll-up	1	¢	_
	1	\$ 161	
   Rear Threshold, Covered with Gray Speedliner 6" W x Full W at Rear doors		\$ 101	
   C/S Stepwell Threshold, Polished Diamond Plate	1	Ş	-
 COT MOUNT HARDWARE: (Full Size Mod)	1	\$	-
   Cot Mount: Stryker, No 6390, Power Load, Installed ILOS	1	\$ 32,334	
mass casualty kit not requested	1	\$	-
Cable Extension for Stryker Powerload System	1	\$ 45	
   12v power feed location FRONT for Stryker power load 6390	1	\$	-
  - Cot Position No 1: PRIMARY SIDE POSITION ONLY	1	Ś	-
   Primary Cot position under floor reinforcement	1	\$	_
		\$	
   Cot mount set up for: Stryker Power-Pro 6506	1	+	-
  - Cot Stop, Block: Stryker Power/Performance load. Install hook with kit	1	\$ 29	
   Q Straint System: NONE	1	\$	-
OXYGEN / AIR / VACUUM System:	1	\$	-
O2 Outlet No 1: Amico Ohmeda Diamond	1	\$	-
LOCATION: Action Area	1	\$	-
   O2 Outlet No 2: Amico Ohmeda Diamond	1	\$	_
   LOCATION: Center Pad of Liner Panel, Over Head/Chest (Non-X Series)	1	\$	_
		+	
   O2 Outlet No 3 Amico Ohmeda Diamond	1	\$ 301	
   LOCATION: Curbside Wall, over the head of the S/B	1	\$	-
   Rack No 1: Zico #QR-MV, ILOS Compliant	1	\$ 404	
Aluminum Cover: Over Front of Oxygen Rack in Bench	1	\$ 140	
Rack Slide Out Bracket QRSOFD2 For Zico #QR-MV -	1	\$ 2,058	
   Cylinder Type: OXYGEN - Green Colored Hose	1	\$	-
   Rack Location: Squad Bench to Slide Out M4 Door	1	\$	_
   Set up For M cylinder	1	\$	_
	1	Ś	
   Zico oxygen tank restraint pull to tighten restraint straps (4) included		\$	
   Regulator, Oxygen: Has VMUX Transducer, Inspected and Installed	1	\$	-
   Regulator Wrench: Cast aluminum, OXYGEN w/ cable lanyard	1	\$	-
   Vacuum System: SSCOR regulator/gauge panel in A/A	1	\$	-
Collection Canister w Clip: Bemis, 1200 CC Capacity -J3043 retention compliant	1	\$	-
   VAC Plumbing: Direct from panel to canister - NO Outlet	1	\$	-
   Vacuum Pump: 49 State	1	\$	-
   Location: M-2 Compartment On Ceiling	1	Ś	-
   Interior window and aluminum trim with standard satin finish- std	1	\$	_
 '	1	+	
 Compartment Door Sill: Stainless Steel From O2 Rack to M4 Door		\$ 113	
 ********DOOR DEPARTMENT - Full Mod***********	1	\$	-
Handles, Ext: Tri-mark 030-1875, Free Float, Polished CNNC finish	1	\$	-
Interior Release: All Entry Doors, with bezel Emergency Access	1	\$	-
Rear Entry Assist Handle not required	1	\$	-
   Grab Rail, C/S wall, Various types C/S Entry, NONE	1	\$	-
 Entry Door Panels, Windows and Hardware	1	\$	-
Interior Grab Handle Color: Yellow Antimicrobial	1	\$	-
   Grab Handle, CS Entry: (1) 3-pt "L" Shaped 90, Yellow Antimicrobial ILOS	1	\$ 239	
   Grab Handles, Rear Access: (2) 3-pt "L" Shaped 90, Yellow Antimicrobial	1	\$ 471	
   Grab Handle, (2), Black, Allegis Corp. #9/01228	2	\$ 271	
   Door Panels: Mica Upper / Smooth Aluminum / Stainless Steel Lower	1	\$ 609	
   Curbside Lower Door Panel: Stainless	1	\$	-
UPPER Windows: RA Doors, Fixed Tinted Glass 17.3"W x 19.3"H	1	\$	-
UPPER Window: CS Access, Fixed Glass, std tint	1	Ś	-
 Solid wall with sliding Lexan window	1	\$	_
	1	\$	_
   Sliding Window Locking Pin: 1/4" with Lanyard		+	-
Dri-Dek Compt Floors and shelves, Black	1	\$ 783	
   Rubber Matt: M7 Compartment Shelves	1	\$ 306	
Radio : Kenwood KDC168U CD/Am/Fm MA/USB: In patient area	1	\$ 586	
		\$ 162	
Customer Supplied Radio Head Bracket Installed in Action Area	1	2 T0Z	
Customer Supplied Radio Head Bracket Installed in Action Area   Blue Sea 5025 Fuse Block for Customer Installed Knox Box Medvault Model 5500	1	\$ 339	
Blue Sea 5025 Fuse Block for Customer Installed Knox Box Medvault Model 5500	1	\$ 339	
Blue Sea 5025 Fuse Block for Customer Installed Knox Box Medvault Model 5500   (1) DC Sub panel Buss Bar with cover 6 circuits Blue Sea 5025	1	\$ 339 \$ 228	
Blue Sea 5025 Fuse Block for Customer Installed Knox Box Medvault Model 5500	1	\$ 339	

   Light Location: Bottom of Cabinet B1	1	\$ -
 Upholstery Color: Light Gray( Dove) Vac form	1	\$ -
Center Trough Upholstery Color: Color Key to Rest of Truck	1	\$ -
Uph Joint Type: Vacuum Formed - Seamless	1	\$ -
Squad Bench seat cushion cut-outs: None	1	\$ -
Head Protection: Pad over CS Entry Door	1	\$ -
Head Protection: 1" Pad over Rear Access Doors, Full Width	1	\$ -
Undercoating : Per QVM Guidelines, STD	1	\$ -
Reflective Tape: White Reflective On Painted edges of Exterior Door Frame	1	\$ -
Compartment Finish: Diamond Plate Standard	1	\$ -
Primary (Over All) Color: Red and Metallic Silver	1	\$ 20,554
Flip Step Reflective/Prismatic Tape: Red/White/R/W/R/W/R	1	\$ -
Tape Stripe: NONE (KKK-F Deviation)	1	\$ -
Non-Compliant toKKK-F 3.16.2 ;Exterior Safety stripe to be Orange	1	\$ -
Roof Color: Same Color as Over All	1	\$ -
Roof Paint: Color and finish quality to be GLOSSY	1	\$ -
Drip Rails: Bright Alum, De-burred & rounded corners (SHIPPED LOOSE)	1	\$ -
Flow Meters: (2) 0-25 LPM Oxygen, Dial Peak W/ Ohmeda adapter #7MFA1105:	2	\$ 581
Flow Meter: 0-25 LPM Oxygen, Dial Peak W/ Ohmeda adapter #7MFA1105TC:	1	\$ 363
Drip Rails:Detail-Refer to Paint Section for Drip Rail Information (Ship Loose)	1	\$ -
(1) Total Red With White Letter Labels 3.5" x 3.5"	1	\$ 43
Owner's Manual USB Flash Drive ship loose	1	\$ -
Install 5 Minute Delay Start Label On Danhard Face Plate	1	\$ 43
Shoreline Labels: Shipped Loose and Not Installed	1	\$ -
Install 3.5" x 3.5" Engraved Label Red With White Letters for DEF Fluid	1	\$ 43
Decals: Install 32" Star of Life on Mod Roof. Chevrons/Grahics with Window Perf	1	\$ 2026
Black Cactus Mat For Buss Bar Covers: Shipped Loose	1	\$ -
DECALS: NO Smoking & Sealbetbelt Decals Installed	1	\$ -
AEV Logos: Installed on unit per AEV standard locations	1	\$ -
Fire Extinguisher, 5 pound, shipped loose, IATS	1	s 174
Fire Extinguisher, 5 pound, shipped loose, Std	1	\$ -
Exception to 3.15.2 Required Two fire extinguishers installed by FSAM	1	\$ -
Exception to C.16.1 1 Required Two fire extinguishers installed by FSAM	1	\$ -
Reflector Pkg: Body - 2ea, Side Fr Amber, Side Rear Red, Rear Red	1	\$ -
Post And Wheel Cups: NONE	1	\$ -
Spare Tire: Refer To Chassis Section to See if it gets one.	1	\$ -
(2) SCBA Bracket: Zico Model KD-UH-6-SF SHIP LOOSE	2	\$ 573
Collision Restraint Strap: ZICO No 1010-120-000 - Ship Loose	2	\$ 388
FLIRK2 Camera with Charger and Lanyard	1	\$ 4,254
Indict 500 w/ Ozone	1	\$ 1,649
Battery Chargers	1	\$ 801
Stryker Power Pro 2 Cot	1	\$ 34,967
Stryker 6252 Stairchair		\$ 5,367
 Total		\$ 480,986